

Emergency Eyewash/Safety Shower Guidelines



Purpose

The Guidelines for Emergency Eyewash and Sa

Emergency Eyewash/Safety Shower Guidelines



Environmental Health & Safety (EHS)

-

Emergency Eyewash/Safety Shower Guidelines



- Flushing fluid shut off valves located

Emergency Eyewash/Safety Shower Guidelines



removal must be automatic (not require a separate motion by the user) when the unit is turned on.

- Eyewash units must be placed between 83.8 cm (33 in) and 114.3 cm (45 in) from the user's standing surface and at least 15.3 cm (6 in) from the nearest wall or other obstruction.


HAND-HELD DRENCH HOSES

- Hand-held drench hoses provide support for EM shcm 204 Tc 0.004

Emergency Eyewash/Safety Shower Guidelines



- Each personal eyewash station/unit must be reviewed regularly to ensure components are in place, the station/unit is readily accessible, and that flushing solution has not passed its expiration date. Also verify that bottles with seals/tamper indicators are intact.



Emergency Eyewash/Safety Shower Guidelines



Sample of Weekly Inspection Tag

Emergency Eyewash/Safety Shower Inspection Record			
If this device passes, indicate the date and the initials of the inspector. If the device fails, contact the Facilities Department and OHS immediately.			
Date	Inspected By	Date	Inspected By